SECTION 1- PRODUCT AND COMPANY IDENTIFICATION

1.1 Product Identifier

Product Name: Pur Stick SDS ID Number PS01

REACH Registration: No data available

1.2 Relevant identified uses of the substance or mixture and uses advised against

General Use One Component Polyurethane Foam Adhesives

Uses advised against

1.3 Details of the supplier and of the safety data sheet

Manufacturer TODOL Products
25 Washington Avenue
Natick MA 01760

Natick, MA 01760 1-800-252-3818

1.4 Emergency telephone numbers

In the U.S.A CHEMTREC (24 hours) 1-800-424-9300 International Emergency CHEMTREC (24 hours) 1-703-527-3887

SECTION 2- HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

Product definition: Mixture

Classification:

Gases Under Pressure- Compressed Gas Acute Toxicity Inhalation- Category 4

Skin Irritation- Category 2

Serious Eye Irritation- Category 2A Respiratory Sensitizing- Category 1 Skin Sensitization – Category 1 Specific Target Organ Toxicity SE 3

Reproductive toxicity- Effects on or via lactation

Specific Target Organ Toxicity RE 2 Aquatic Chronic- Category 4

2.2 Label elements Hazard Symbols:



Signal Word: Hazard Statements:

WARNING

H280- Contains gas under pressure; may explode if heated

H315- Causes Skin Irritation

H317- May cause an allergic skin reaction H319- Causes Serious Eye Irritation

H332- Harmful if inhaled

H334- May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335- May cause respiratory irritation H362- May cause harm to breastfed children

H373- May cause damage to organs through prolonged or repeated exposure

H413- May cause long lasting harmful effects to aquatic life

Prevention: P102- Keep Out of Reach of Children

P202- Do not handle until all safety precautions have been read and understood

P251- Pressurized Container: Do not pierce or burn, even after use

P261- Avoid breathing vapors or fumes

P262- Do not get in eyes, on skin, or on clothing

P264- Wash hands and other skin areas exposed to material thoroughly after handling

P271- Use only outdoors or in a well-ventilated area

P273- Avoid release to the environment

P280- Wear protective gloves, protective clothing and eye protection P285- In case of inadequate ventilation wear respiratory protection

LP PU FOAM ADHESIVES 134A ISSUE DATE: March 2005 LAST REV: February 2015 PAGE 2 OF 7

Response: P302+P352+P333+P313 IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get

medical attention

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing

P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. P314- Get medical advice if you feel unwell

P342+P311- If experiencing respiratory symptoms: Call a POISON CENTER or doctor

P381- Eliminate all ignition sources if safe to do so

Storage: P403+P405- Store in a well-ventilated place. Store locked up.

P410- Protect from sunlight

P412- Do not expose to temperatures exceeding 50°C/122°F.

Disposal: P501 Dispose of contents/container in accordance with applicable local/regional/national/international

regulations.

SECTION 3- COMPOSITION/INFORMATION ON INGREDIENTS

% by	Ingredient	CAS No.	EC Number	Annex Number	EC Classification
Weight					
	Urethane Pre-Polymer Blend (Non-	Proprietary			
60-100	Hazardous Polyol Blend)				
10-30	1,1,1,2 Tetrafluoroethane	811-97-2	217-377-0		
5-10	4,4' Diphenylmethane diisocyanate (MDI)	101-68-8	202-966-0	615-005-00-9	Car. Cat 3, R40; Xn R20, R48/20; Xi R36/37/37, R42/43
5-10	Polymethylene polyphenyl isocyanate (PMDI)	9016-87-9	500-079-6		
5-10	Alkanes, C14-C17, Chloro	85535-85-9	287-477-0	602-095-00-X	R53; R64

There are not additional ingredients present which, within the current knowledge of the supplier and in the concentration applicable, are classified as hazardous to the health or environment and hence require reporting in this section.

SECTION 4- FIRST AID MEASURES

4.1 Description of first aid measures

Eye: Immediately flush eyes with large amounts of water for at least 15 minutes, holding the eyes open with fingers and

occasionally lifting the upper and lower lids. Use lukewarm water if possible. If present and easy to do so, remove contact

lenses, If irritation persists, get medical attention.

Skin: In case of contact, immediately flush skin with plenty of soap and water. Foam will stick to skin, gently wipe product from skin

with a damp cloth and wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash clothing before

reuse. Call a physician if irritation persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Obtain medical

attention.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an

unconscious person. Get medical advice/attention.

4.2 Most important symptoms and effects, both acute and delayed

Eye: May cause eye irritation.

Skin: May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause an

allergic reaction. Prolonged skin exposure is unlikely to result in absorption of harmful amounts

Inhalation May be harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if

inhaled. Inhalation of propellant may cause headache, lightheadedness and lethargy.

Ingestion: May be harmful if swallowed. May cause gastrointestinal irritation: stomach distress, nausea, or vomiting.

Chronic: Chlorinated paraffin (C14-c17) may cause harm to breastfed children. Refer to section 12.2

4.3 Notes to the physician

Symptoms may not appear immediately. If case of an accident or if you feel unwell, seek medical advice immediately (show label or SDS if possible).

LP PU FOAM ADHESIVES 134A ISSUE DATE: March 2005 LAST REV: February 2015 PAGE 3 OF 7

SECTION 5- FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable methods of extinction: Use dry chemical, carbon dioxide, foam, Halon 1211 and water spray or fog. **Unsuitable methods of extinction**: Do not use water jets and high pressure water as these may spread the fire

5.2 Special hazards arising from the substance or mixture

Contains compressed gas. Eliminate all ignition sources. Closed containers may explode due to buildup of pressure when exposed to extreme heat. Aerosol cans exposed to fire or high temperature can rupture and rocket. Cured foam will burn in the presence of heat, oxygen and an ignition source.

5.3 Advice to firefighters

Products of combustion: May include and are not limited to: oxides of carbon, oxides of nitrogen, hydrogen fluoride, and traces of hydrogen cyanide.

Keep upwind of fire. Wear full fire-fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Containers may explode if heated.

SECTION 6- ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2 Environmental precautions

Do not allow to enter sewers, drains, or waterways

6.3 Methods and materials for containment and cleaning up

Method for containment: Uncured product is very sticky; carefully remove the bulk of the foam by scraping it up and then immediately remove the residue with a rag and solvent such as Handi-Cleaner, mineral spirits, acetone (nail polish remover), paint thinner, etc. Once the product is cured it can only be removed mechanically by scraping, buffing, etc. Use appropriate PPE.

Methods for cleaning up: Scoop up material and place in a disposal container. Dispose of as plastic waste in accordance with all applicable guidelines and regulations. Vapors can accumulate in low areas. Provide ventilation

6.4 Reference to other sections

For indications about waste treatment, see Section 13

SECTION 7- HANDLING AND STORAGE

7.1 Precautions for safe handling

Pressurized container: do not pierce or burn, even after use. Container may explode if heated. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Do not swallow. Use only in a well-ventilated area or outdoors. Avoid welding or other "hot work" in the vicinity of exposed cured foam. When using do not eat, drink or smoke. (See section 8)

General hygiene advice: Launder contaminated clothing before reuse. Wash hands before eating, drinking or smoking.

7.2 Conditions for safe storage including any incompatibilities

Store in a dry place. Ideal use temperature is 65°F to 80°F (18°C to 27°C). Do not expose aerosol cans to open flame or store at temperatures above 122°F (50°C). Excessive heat can cause premature aging of components resulting in a shorter shelf life. Storage below 55°F (12.7°C) may affect foam quality if chemicals are not warmed to room temperature before using. Protect containers from physical abuse. Keep containers upright. **KEEP AWAY FROM CHILDREN.**

SECTION 8- EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Control Parameters

CAS No.	Ingredient	OSHA-PEL TWA	ACGIH-TLV	NIOSH/ Other
101-68-8	4,4' Diphenylmethane diisocyanate	0.02 PPM; 0.2 mg/m ³ Ceiling	0.005 ppm; 0.051 mg/ m ³ (8 hours) TWA	0.005 ppm; 0.050 mg/m ³ TWA 0.02 ppm; 0.2 mg/m ³ CEIL
811-97-2	1,1,1,2 Tetrafluoroethane			WEEL 1,000 ppm

8.2 Exposure Controls:

Engineering measures: Use ventilation adequate to keep exposures below recommended exposure limits.

Eye/face Protection: Wear protective safety glasses with side shields or goggles.

Hand Protection: Use chemically resistant gloves (i.e. Nitrile gloves). Nitrile/butadiene rubber, butyl rubber, polyethylene, PVC (vinyl), or neoprene gloves are also effective. Glove selection should take into account potential body reactions to certain materials and manufacturer's instructions for use. Break through time of selected gloves must be greater than the intended use period.

Other Protective Equipment: Use clothing that protects against dermal exposure. Appropriate protective clothing varies depending on the

potential for exposure. To ensure proper skin protection, wear PPE in such a manner that no skin is exposed.

Respiratory Protection: If atmospheric levels are expected to exceed the exposure levels, use a NIOSH approved air purifying respirator equipped with an organic vapor cartridge and particulate filter. If atmospheric levels exceed 10 times the TLV or PEL level for which an airpurifying respirator is effective, use a powered air purifying respirator (PAPR). The type of respiratory protection selected must comply with the requirements set forth in OSHA's Respiratory Protection Standard (29 CFR 1910.134).

Hygiene Measures: An eye wash station or portable eye wash station should be in the area. Wash hands thoroughly after use, before eating, drinking or using the lavatory. Employees/Users should be educated and trained in the safe use and handling of this product.

SECTION 9- Physical and chemical properties

9.1 Information on basic physical and chemical properties					
General Physical Form	Viscous liquid which forms off-white to yellowish foam upon release.				
Color	Crème. Some products contain a dye or colorant.				
Odor	Slight fluorocarbon odor during curing stage				
Odor Threshold:	No data available				
Physical State:	Gas/Pressurized Liquid/Semi-Solid				
pH:	No data available				
Melting Point/Freezing Point	No data available				
Initial Boiling Point and Boiling Range	HFC-134A boils at -26°C (-15°F). Other components boil at 93.3°C (200°F)				
Flash Point:	Use of non-flammable propellant				
Evaporation Rate:	No data available				
Flammability:	Flammable				
Lower Flammability/Explosive Limit:	No data available				
Upper Flammability/Explosive Limit:	No data available				
Vapor Pressure	Aerosol product > 50 psig/ 345 kPa				
	Final product (sprayed): Very low (not determined)				
Vapor Density:	Not available				
Relative Density/Specific Gravity:	~ 1.1 (Water = 1)				
Solubility:	Insoluble; reacts slowly with water during cure, liberating traces of CO ₂				
Partition coefficient: n-octanol/water:	No data available				
Auto-ignition Temperature:	No data available				
Decomposition Temperature;	No data available				
Viscosity:	No data available				
Oxidizing Properties:	No data available				
VOC Content (calculated minus exempt	0 g/l minus exempted compounds				
compounds and water)					

SECTION 10- STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical Stability

Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not pierce or burn, even after use. Avoid temperatures below $40^{\circ}F$ ($4^{\circ}C$). For longest shelf life, avoid storage above $100^{\circ}F$ ($38^{\circ}C$).

10.3 Possibility of Hazardous Reactions

Elevated temperatures can cause product to decompose, releasing carbon dioxide. Flammable propellant. Contents are under pressure and exposure to high temperature can cause containers to rupture or explode.

10.4 Conditions To Avoid

Heat. Incompatible materials. Sources of ignition. Avoid temperatures below 40°F (4°C) or temperatures above 100°F (38°C).

10.5 Incompatible Materials

Alcohols, strong bases, amines, metal compounds, ammonia, and strong oxidizers.

10.6 Hazardous Decomposition Products

May include, and are not limited to: oxides of carbon, oxides of nitrogen, hydrogen fluoride and traces of hydrogen cyanide.

SECTION 11- TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological effects:

Acute Oral Toxicity

Expected to have low acute oral toxicity

Acute inhalation toxicity

Expected to have low acute inhalation toxicity

Acute dermal toxicity

Expected to have low acute dermal toxicity

Skin irritation

Causes skin irritation

Eve irritation

Causes serious eve irritation

Sensitization

May cause skin and respiratory sensitization

Genotoxicity

Genetic toxicity data for MDI is inconclusive. Some in-vitro studies yielded positive results, while other test data was negative

Mutagenicity

Test data using laboratory animals was predominately negative

Specific organ toxicity- single exposure

May cause respiratory irritation

Specific organ toxicity- repeated exposure

May cause damage to the lungs, central nervous system and skin

Aspiration hazard

No data available

11.2 Delayed, Immediate, and Chronic Effects of Short and Long Term Exposure

MDI and PMDI: IARC Group 3 carcinogen- Not classifiable as to its carcinogenicity to humans. Not listed as a carcinogen by ACGIH, OSHA or NTP. MDI/PMDI did not cause birth defects in laboratory animals; fetal effects occurred only at high doses which were toxic to the mother. Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/PMDI (6mg/m³) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects. Chlorinated paraffins (C14-C16) may accumulate in body tissues and fluids rich in lipid content; therefore, this material may cause harm to breastfed children.

SECTION 12- ECOLOGICAL INFORMATION

12.1 Ecotoxicity

The aquatic toxicity of this product has not been experimentally determined. However, it is expected to have low acute aquatic toxicity based on the acute aquatic toxicity of the individual components and their concentration in this mixture.

12.2 Persistence and degradability

Product is not readily biodegradable. In aquatic and terrestrial environments, this material reacts with water, which forms predominately insoluble polyureas.

12.3 Bioaccumulative potential

Bioaccumulation potential is low

12.4 Mobility in soil

Expected to have low mobility based on product's reactivity with water

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other Adverse Effects

No data available

SECTION 13- DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Methods of disposal

Before disposing of containers, relieve container of any remaining foam and pressure. Allow dispensed product to fully cure before disposing. Never discard in a liquid state. This material must be disposed of in accordance with all local, regional, national, international regulations.

Other disposal recommendations:

Do not puncture or incinerate containers. Use appropriate Personal Protective Equipment.

SECTION 14-TRANSPORTATION

Shipping Information

	Containers 1000 cu. cm. (1 liter) or less:	Due to changes in December 2020: See shipping papers for exact 49 CFR descriptions.	Containers Greater Than 1000 cu. cm. (1 liter):
Ground	Consumer Commodity ORM-D	Limited Quantity	UN1956 Compressed Gas n.o.s (Fluorinated hydrocarbon, Nitrogen) 2.2 (Non-flammable Gas Label)
Air	UN1950 Aerosols, Non-Flammable 2.2 (Non-Flammable Gas Label) LIMITED QUANTITY Packing Instructions (Cargo & Passenger) 203	UN1950 Aerosols, Non-Flammable 2.2 (Non-Flammable Gas Label) LIMITED QUANTITY Packing Instructions (Cargo & Passenger) 203	UN1956 Compressed Gas n.o.s (Fluorinated hydrocarbon, Nitrogen) 2.2 (Non-flammable Gas Label)
Water	UN1950 Aerosols, Non-Flammable 2.2 (Non-Flammable Gas Label) LIMITED QUANTITY	UN1950 Aerosols, Non-Flammable 2.2 (Non-Flammable Gas Label) LIMITED QUANTITY	UN1956 Compressed Gas n.o.s (Fluorinated hydrocarbon, Nitrogen) 2.2 (Non-flammable Gas Label)

SECTION 15- REGULATORY

15.1 Safety, health, and environmental regulations/ legislations specific for the substance or mixture <u>U.S. Federal Regulations</u>

OSHA Hazard Communication Standard: This material is classified as a hazardous in accordance with OSHA 29 CFR 1910-1200 **TSCA Status:** All components of this product are listed on the Toxic Substance Control Act (TSCA) Inventory. This product is not subject to TSCA 12(b) Export Notification.

Superfund Amendments and Reauthorization Act (SARA)

SARA Section 311/312 Hazard Categories: Acute Health Hazard, Chronic Health Hazard, Reactive Hazard, Sudden Release of Pressure Hazard

SARA 313 Information: MDI and PMDI are subject to reporting levels established by Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986.

SARA 302/304 Extremely Hazardous Substance: No components of the product exceed the threshold (de minimis) reporting levels established by these sections of the Title III of SARA.

SARA 302/304 Emergency Planning & Notification: No components of the product exceed the threshold (de minimis) report levels established by these sections of the Title III of SARA.

Comprehensive Response Compensation and Liability Act (CERCLA): This product contains the following CERCLA reportable substances: 4,4'- Diphenylmethane diisocyanate (CAS #101-68-8), RQ- 2,268 kg (5,000 lbs).

Clean Air Act (CAA) - 4,4'- Diphenylmethane diisocyanate (CAS #101-68-8) is listed as a Hazardous Air Pollutant (HAP) designated in CAA Section 112 (b). This product does not contain any Class 1 or Class 2 Ozone depletors.

Clean Water Act (CWA) - 4,4'- Diphenylmethane diisocyanate (CAS #101-68-8) is listed as a Hazardous Substance under the CWA. None of the chemicals in these products are listed as Priority Pollutants under the CWA. None of the chemicals listed in these products are listed as Toxic Pollutants under the CWA.

U.S. State Regulations:

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains trace amount of substances known to the State of California to cause cancer or other reproductive harm.

Other U.S. State Inventories:

4, 4'- Diphenylmethane diisocyanate (CAS #101-68-8) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/air Pollutants lists: CA, DE, ID, IL, ME, MA, MN, NJ, PA, WA, WI

Polymeric MDI (CAS #9016-87-9) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists: DE, NJ, MN

1,1,1,2 Tetrafluoroethane (CAS #811-97-2) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists: ME, WI

LAST REV: February 2015

Canada

WHMIS Hazard Symbol and Classification:



A- Compressed Gas

D2A- Very toxic material causing other toxic effects (Respiratory Sensitizer)
D2B- Toxic Material causing other toxic effects (Skin Sensitizer) (Skin/Eye Irritant)

Canada Controlled Product Regulations (CPR): This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation, and the SDS contains all the information required by the Controlled Products Regulations.

Canadian Ingredient Disclosure List (IDL): 4,4'- Diphenylmethane diisocyanate (CAS #101-68-8) is listed on the IDL.

Canadian National Pollutant Release Inventory (NPRI): MDI and PMDI are listed on the NPRI

European Economic Community

Labeling (67/548/EEC or 1999/45/EC)



Xn- Harmful

Risk Phrases: R20- Harmful by inhalation

R36/37/38- Irritating to eyes, respiratory system and skin

R40- Limited evidence of carcinogenic effect

R42/43- May cause sensitization by inhalation and skin contact

R48/20- Harmful: danger or serious damage to health by prolonged exposure through inhalation.

R64- May cause harm to breastfed babies

R53- May cause long-term adverse effects in the aquatic environment

Safety S1/2- Keep locked up and out of reach of children

Phrases: S23- Do not breathe fumes, vapor, or mist

S36/37- Wear suitable protective clothing and gloves

S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label or this SDS where

possible.

WGK, Germany (Water danger/protection): 1

Global Chemical Inventory Lists:

United States: Toxic Substance Control Act (TSCA)- Yes

Canada: Domestic Substances List (DSL)- Yes Canada: Non-Domestic Substances List (NDSL)- No

Europe: Inventory of New and Existing Chemicals- (EINECS)- Yes Australia: Australian Inventory of Chemical Substances (AICS)- Yes New Zealand: New Zealand Inventory of Chemicals (NZLoC)- Yes China: Inventory of Existing Chemical Substances in China (IECSC)- Yes Japan: Inventory of Existing and New Chemical Substances (ENCS)- Yes

Korea: Existing Chemicals List (ECL)- Yes

15.2 Chemical safety assessment: For this product a chemical safety assessment was not carried out

SECTION 16- OTHER

NFPA: Health Hazard 2; Flammability 1; Reactivity 1 HMIS: Health Hazard 2; Flammability 1; Physical Hazard 1

Hazard Rating: 0=minimal, 1= slight, 2=moderate, 3=severe, 4= extreme

The information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof. The manufacturer makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. No representations or warranties, either expressed or implied, of merchantability or fitness for a particular use are made hereunder with respect to this information or the product to which information refers.

Information contained herein is deemed to be reliable, conservative and accurate. Fomo Products, Inc. reserves the right to change the design, specifications or any other features at any time and without notice, while otherwise maintaining regulatory compliance.

Revision-February 4, 2015 Version 2.0 (Replaces Version 1.7- June 29, 2012)